



## Art.2 5 DIN5157 BSW Pipe Taps

DIN5157, for Whitworth-Pipe thread DIN259, equal to ISO 228

M2 HSS

M35 HSS-E, Coating, available for specified requirements

2 of set: Taper and Plug.

For through holes and blind holes

For connections not sealing in the thread

| Code    | Size          | T.P.I | D(mm) | L(mm) | Lc(mm) | d(mm) | K(mm) | Hole(mm) |
|---------|---------------|-------|-------|-------|--------|-------|-------|----------|
| 2510100 | <b>G1/8</b>   | 28    | 9.73  | 63    | 20     | 7     | 5.5   | 8.80     |
| 2510110 | <b>G1/4</b>   | 19    | 13.16 | 70    | 20     | 11    | 9     | 11.8     |
| 2510120 | <b>G3/8</b>   | 19    | 16.66 | 70    | 22     | 12    | 9     | 15.3     |
| 2510130 | <b>G1/2</b>   | 14    | 20.96 | 80    | 22     | 16    | 12    | 19.0     |
| 2510140 | <b>G5/8</b>   | 14    | 22.91 | 80    | 22     | 18    | 14.5  | 21.0     |
| 2510150 | <b>G3/4</b>   | 14    | 26.44 | 90    | 22     | 20    | 16    | 24.5     |
| 2510160 | <b>G7/8</b>   | 14    | 30.20 | 90    | 22     | 22    | 18    | 28.25    |
| 2510170 | <b>G1</b>     | 11    | 33.25 | 100   | 25     | 25    | 20    | 30.5     |
| 2510180 | <b>G1 1/8</b> | 11    | 37.90 | 125   | 40     | 28    | 22    | 35.5     |
| 2510190 | <b>G1 1/4</b> | 11    | 41.91 | 125   | 40     | 32    | 24    | 39.5     |
| 2510200 | <b>G1 3/8</b> | 11    | 44.33 | 125   | 40     | 36    | 29    | 42.0     |
| 2510210 | <b>G1 1/2</b> | 11    | 47.81 | 140   | 40     | 36    | 29    | 45.0     |
| 2510220 | <b>G1 3/4</b> | 11    | 53.75 | 140   | 40     | 40    | 32    | 51.0     |
| 2510230 | <b>G2</b>     | 11    | 59.62 | 160   | 40     | 45    | 35    | 57.0     |